



Lithium Metal Cells/Batteries
[passed UN Test Criteria]

Lithium Metal Batteries are classified by function of the Lithium metal content in the cell/battery

Batteries for Transport	Lithium Metal Content	Classification	Labels	Documentation
By Themselves	Cells ≤1g	UN3090 PI 968 Section II	Not more than 1 Package per shipment/AWB Limit per package: ≤0.3g = 2.5kg; or for cells >0.3g ≤1g = 8 cells; or for batteries >0.3g ≤2g = 2 batteries 	A Shipper's Declaration for Dangerous Goods is not required. The words "Lithium ion batteries in compliance with Section II of PI 968" and "Cargo Aircraft Only" or "CAO" must be included on the air waybill.
	Batteries ≤2g			
PAX A/C	Cells >1g	UN3090 PI 968 Section IA CAO: 35 kg		
	Batteries >2g			
Contained in Equipment	Cells ≤1g	UN3091 PI 970 Section II	PAX A/C: 5 kg CAO: 5 kg 	A Shipper's Declaration for Dangerous Goods is not required. Where a consignment includes packages bearing the lithium battery mark, the words "Lithium ion batteries in compliance with Section II of PI 970" must be included on the air waybill.
	Batteries ≤2g			
	Cells >1g	UN3091 PI 970 Section I	PAX A/C: 5 kg CAO: 35 kg 	
	Batteries >2g			
Packed with Equipment	Cells ≤1g	UN3091 PI 969 Section II	PAX A/C: 5 kg CAO: 5 kg 	A Shipper's Declaration for Dangerous Goods is not required. The words "Lithium ion batteries in compliance with Section II of PI 969" must be included on the air waybill.
	Batteries ≤2g			
	Cells >1g	UN3091 PI 969 Section I	PAX A/C: 5 kg CAO: 35 kg 	
	Batteries >2g			

